

LED CUSEC Anbauleuchte

- › direkt strahlend
- › Acrylabdeckung in opal
- › aus scharfkantig gezogenem Aluminiumprofil
- › Oberfläche pulverbeschichtet

- › LED in SMD-Technologie,
2-Step MacAdam, L80/B10 – 50000 h

- › Low Flux LED-Typ 13
- › Mid Flux LED-Typ 14
- › High Flux LED-Typ 15



opal, direkt

H 40		
H 100		
H 100		
H 100		
H 100		

Lichtstrom High Efficiency (CRI > 82)

Artikel	LED-Typ	3000 K	4000 K	Leistung
18112	13	1050 lm	1080 lm	12 W
	14	1470 lm	1520 lm	15 W
	15	2080 lm	2160 lm	20 W
18113	13	1570 lm	1630 lm	16 W
	14	2200 lm	2280 lm	21 W
	15	3120 lm	3240 lm	29 W
18114	13	2100 lm	2170 lm	20 W
	14	2940 lm	3050 lm	27 W
	15	4160 lm	4330 lm	37 W
18115	13	2620 lm	2720 lm	24 W
	14	3670 lm	3810 lm	33 W
	15	5200 lm	5410 lm	46 W
18116	13	3150 lm	3260 lm	28 W
	14	4410 lm	4570 lm	38 W
	15	6250 lm	6490 lm	54 W